



# VO-60 Lubricant

## Product Description

A vanishing oil lubricant designed for stamping, drawing and piercing operations. This light oil formulation provides lubrication during forming and completely evaporates to leave no residual. VO-60 is ideal for jobs which require a “dry the touch” residual.

## Typical Properties

Appearance ..... Clear, colorless liquid  
Density ..... 6.4 lbs/gallon  
Flash Point ..... >150° F (TCC)

## Application

Brush, roll coat, or drip on the following substrates: cold/hot rolled steel, hot dip/EG galvanized, stainless steel, aluminum, copper and brass.

## Use Directions

Metal Mates VO-60 is supplied ready to use.

## Safety and Handling

Combustible: Keep away from flames, sparks, or hot surfaces. Avoid contact with eyes and prolonged contact with the skin. Wash thoroughly after handling. Minimum contact with this and all chemicals is a good policy to follow along with reading the Material Safety Data Sheet.

## Storage

Indoor storage preferred. First in first out stock rotation is recommended.

## Container Size

5 gallon pails, 55 gallon drums and 330 gallon totes.

**TW** **ROCOL® North America**

3624 West Lake Avenue · Glenview, IL 60026

Tel (800) 452-5823 · Fax (800) 952-5823

Tel (800) 657-5278 · Fax (800) 657-4897

[www.rocolnorthamerica.com](http://www.rocolnorthamerica.com)